



QIIA.E513460 - PHOTOVOLTAIC MODULES AND PANELS WITH SYSTEM VOLTAGE RATINGS OVER 600 VOLTS

Photovoltaic Modules and Panels with System Voltage Ratings Over 600 Volts

See General Information for Photovoltaic Modules and Panels with System Voltage Ratings Over 600 Volts

MYSOLAR MANUFACTURING (SHANGHAI) CO LTD
 ROOM J8097, BLDG 2, NO. 4268, ZHENNAN RD, JIADING DISTRICT
 201802 SHANGHAI, CHINA

E513460

Cat. No.	Electrical and Module Fire Class and Type Ratings					
	Isc	Voc	Pmax	Max System V dc	Series Fuse Rating (A)	Module Fire Performance Type Rating
Photovoltaic module						
MS315P-ASX "X"=1	8.91	45.6	315	1500	20	1
MS320P-ASX "X"=1	9.03	45.82	320	1500	20	1
MS325P-ASX "X"=1	9.15	45.92	325	1500	20	1
MS330P-ASX "X"=1	9.28	45.97	330	1500	20	1
MS335P-ASX "X"=1	9.3	46.45	335	1500	20	1
MS315P-ASX "X"=3	8.91	45.6	315	1500	20	1
MS320P-ASX "X"=3	9.03	45.82	320	1500	20	1
MS325P-ASX "X"=3	9.15	45.92	325	1500	20	1
MS330P-ASX "X"=3	9.28	45.97	330	1500	20	1
MS335P-ASX "X"=3	9.3	46.45	335	1500	20	1
MS265P-ASX "X"=1; MS265P-ASX "X"=3	9.1	38.14	265	1500	20	1
MS270P-ASX "X"=1, MS270P-ASX "X"=3	9.15	38.31	270	1500	20	1
MS275P-ASX "X"=1, MS275P-ASX "X"=3	9.24	38.5	275	1500	20	1
MS335M-ASX "X"=1, MS335M-ASX "X"=3	9.41	46.04	335	1500	20	1
MS340M-ASX "X"=1, MS340M-ASX "X"=3	9.48	46.16	340	1500	20	1
MS345M-ASX "X"=1, MS345M-ASX "X"=3	9.51	46.61	345	1500	20	1
MS350M-ASX "X"=1, MS350M-ASX "X"=3	9.58	46.89	350	1500	20	1
MS355M-ASX "X"=1, MS355M-ASX "X"=3	9.66	47.16	355	1500	20	1
MS360M-ASX "X"=1, MS360M-ASX "X"=3	9.73	47.44	360	1500	20	1
MS365M-ASX "X"=1, MS365M-ASX "X"=3	9.81	47.67	365	1500	20	1
MS370M-ASX "X"=1, MS370M-ASX "X"=3	9.89	47.91	370	1500	20	1
MS375M-ASX "X"=1, MS375M-ASX "X"=3	9.95	48.16	375	1500	20	1
MS290M-AHX "X"=1, MS290M-AHX "X"=3	9.59	38.87	290	1500	20	1
MS295M-AHX "X"=1, MS295M-AHX "X"=3	9.68	39.05	295	1500	20	1
MS300M-AHX "X"=1, MS300M-AHX "X"=3	9.77	39.23	300	1500	20	1
MS305M-AHX "X"=1, MS305M-AHX "X"=3	9.86	39.42	305	1500	20	1
MS310M-AHX "X"=1, MS310M-AHX "X"=3	9.95	39.58	310	1500	20	1

[Cookies on UL](#)
 We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners.. [Learn More](#)

[Cookie Settings](#)

Accept

MS315M-AHX "X"=1, MS315M-AHX "X"=3	10.04	39.74	315	1500	20	1
MS320M-AHX "X"=1, MS320M-AHX "X"=3	10.13	39.92	320	1500	20	1
MS325M-AHX "X"=1, MS325M-AHX "X"=3	10.43	40.1	325	1500	20	1
MS330M-AHX "X"=1, MS330M-AHX "X"=3	10.51	40.27	330	1500	20	1
MS335M-AHX "X"=1, MS335M-AHX "X"=3	10.6	40.44	335	1500	20	1
MS340M-AHX "X"=1, MS340M-AHX "X"=3	10.69	40.62	340	1500	20	1
MS355M-AHX "X"=1, MS355M-AHX "X"=3	9.6	46.82	355	1500	20	1
MS360M-AHX "X"=1, MS360M-AHX "X"=3	9.69	47.01	360	1500	20	1
MS365M-AHX "X"=1, MS365M-AHX "X"=3	9.77	47.21	365	1500	20	1
MS370M-AHX "X"=1, MS370M-AHX "X"=3	9.85	47.4	370	1500	20	1
MS375M-AHX "X"=1, MS375M-AHX "X"=3	9.93	47.61	375	1500	20	1
MS380M-AHX "X"=1, MS380M-AHX "X"=3	10.01	47.8	380	1500	20	1
MS385M-AHX "X"=1, MS385M-AHX "X"=3	10.08	48	385	1500	20	1
MS390M-AHX "X"=1, MS390M-AHX "X"=3	10.48	48.18	390	1500	20	1
MS395M-AHX "X"=1, MS395M-AHX "X"=3	10.56	48.37	395	1500	20	1
MS400M-AHX "X"=1, MS400M-AHX "X"=3	10.64	48.55	400	1500	20	1
MS405M-AHX "X"=1, MS405M-AHX "X"=3	10.71	48.73	405	1500	20	1
MS410M-AHX "X"=1, MS410M-AHX "X"=3	10.79	48.91	410	1500	20	1

Trademark and/or Tradename: **Mysolar**

Last Updated on 2020-03-03

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

Cookies on UL

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners.. [Learn More](#)

› [Cookie Settings](#)

✓ Accept



QIA7.E513460 - PHOTOVOLTAIC MODULES AND PANELS WITH SYSTEM VOLTAGE RATINGS OVER 600 VOLTS CERTIFIED FOR CANADA

Photovoltaic Modules and Panels with System Voltage Ratings Over 600 Volts Certified for Canada

See General Information for Photovoltaic Modules and Panels with System Voltage Ratings Over 600 Volts Certified for Canada

MYSOLAR MANUFACTURING (SHANGHAI) CO LTD
 ROOM J8097, BLDG 2, NO. 4268, ZHENNAN RD, JIADING DISTRICT
 201802 SHANGHAI, CHINA

E513460

Cat. No. Electrical and Module Fire Class and Type Ratings


Photovoltaic module	I _{sc}	V _{oc}	P _{max}	Max System V _{dc}	Series Fuse Rating	Fire Type Rating
MS315P-ASX "X"=1	8.91	45.6	315	1500	20	1
MS320P-ASX "X"=1	9.03	45.82	320	1500	20	1
MS325P-ASX "X"=1	9.15	45.92	325	1500	20	1
MS330P-ASX "X"=1	9.28	45.97	330	1500	20	1
MS335P-ASX "X"=1	9.3	46.45	335	1500	20	1
MS315P-ASX "X"=3	8.91	45.6	315	1500	20	1
MS320P-ASX "X"=3	9.03	45.82	320	1500	20	1
MS325P-ASX "X"=3	9.15	45.92	325	1500	20	1
MS330P-ASX "X"=3	9.28	45.97	330	1500	20	1
MS335P-ASX "X"=3	9.3	46.45	335	1500	20	1
MS265P-ASX "X"=1; MS265P-ASX "X"=3	9.1	38.14	265	1500	20	1
MS270P-ASX "X"=1, MS270P-ASX "X"=3	9.15	38.31	270	1500	20	1
MS275P-ASX "X"=1, MS275P-ASX "X"=3	9.24	38.5	275	1500	20	1
MS335M-ASX "X"=1, MS335M-ASX "X"=3	9.41	46.04	335	1500	20	1
MS340M-ASX "X"=1, MS340M-ASX "X"=3	9.48	46.16	340	1500	20	1
MS345M-ASX "X"=1, MS345M-ASX "X"=3	9.51	46.61	345	1500	20	1
MS350M-ASX "X"=1, MS350M-ASX "X"=3	9.58	46.89	350	1500	20	1
MS355M-ASX "X"=1, MS355M-ASX "X"=3	9.66	47.16	355	1500	20	1
MS360M-ASX "X"=1, MS360M-ASX "X"=3	9.73	47.44	360	1500	20	1
MS365M-ASX "X"=1, MS365M-ASX "X"=3	9.81	47.67	365	1500	20	1
MS370M-ASX "X"=1, MS370M-ASX "X"=3	9.89	47.91	370	1500	20	1
MS375M-ASX "X"=1, MS375M-ASX "X"=3	9.95	48.16	375	1500	20	1
MS290M-AHX "X"=1, MS290M-AHX "X"=3	9.59	38.87	290	1500	20	1
MS295M-AHX "X"=1, MS295M-AHX "X"=3	9.68	39.05	295	1500	20	1
MS300M-AHX "X"=1, MS300M-AHX "X"=3	9.77	39.23	300	1500	20	1

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media advertising and analytics partners. [Learn More](#)

[Cookie Settings](#)

Accept

MS305M-AHX "X"=1, MS305M-AHX "X"=3	9.86	39.42	305	1500	20	1
MS310M-AHX "X"=1, MS310M-AHX "X"=3	9.95	39.58	310	1500	20	1
MS315M-AHX "X"=1, MS315M-AHX "X"=3	10.04	39.74	315	1500	20	1
MS320M-AHX "X"=1, MS320M-AHX "X"=3	10.13	39.92	320	1500	20	1
MS325M-AHX "X"=1, MS325M-AHX "X"=3	10.43	40.1	325	1500	20	1
MS330M-AHX "X"=1, MS330M-AHX "X"=3	10.51	40.27	330	1500	20	1
MS335M-AHX "X"=1, MS335M-AHX "X"=3	10.6	40.44	335	1500	20	1
MS340M-AHX "X"=1, MS340M-AHX "X"=3	10.69	40.62	340	1500	20	1
MS355M-AHX "X"=1, MS355M-AHX "X"=3	9.6	46.82	355	1500	20	1
MS360M-AHX "X"=1, MS360M-AHX "X"=3	9.69	47.01	360	1500	20	1
MS365M-AHX "X"=1, MS365M-AHX "X"=3	9.77	47.21	365	1500	20	1
MS370M-AHX "X"=1, MS370M-AHX "X"=3	9.85	47.4	370	1500	20	1
MS375M-AHX "X"=1, MS375M-AHX "X"=3	9.93	47.61	375	1500	20	1
MS380M-AHX "X"=1, MS380M-AHX "X"=3	10.01	47.8	380	1500	20	1
MS385M-AHX "X"=1, MS385M-AHX "X"=3	10.08	48	385	1500	20	1
MS390M-AHX "X"=1, MS390M-AHX "X"=3	10.48	48.18	390	1500	20	1
MS395M-AHX "X"=1, MS395M-AHX "X"=3	10.56	48.37	395	1500	20	1
MS400M-AHX "X"=1, MS400M-AHX "X"=3	10.64	48.55	400	1500	20	1
MS405M-AHX "X"=1, MS405M-AHX "X"=3	10.71	48.73	405	1500	20	1
MS410M-AHX "X"=1, MS410M-AHX "X"=3	10.79	48.91	410	1500	20	1

Trademark and/or Tradename: 

Last Updated on 2020-03-03

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

Cookies on UL

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners.. [Learn More](#)

[› Cookie Settings](#)

[Accept](#)